



BLUESUNPV

THREE PHASE
BSM SERIES

BSM125K-B
PV On-Grid String Inverter

125 KW



- 

Max. PV Voltage up to 1100V
Type II DC /AC SPD
- 

PLC communication
WiFi / 4G Plug Optional
- 

DC/AC Ratio up to 1.5
IP66 Protection
- 

High Efficiency up to 98.7%
Smaller and Lighter

YOUR BEST PV SUPPLIER

www.bluesunpv.com

MODEL		BSM125K-B
Input(DC)	Max.DC Voltage	1100V
	Max.Input Current Per MPPT	40A
	Max.Short-circuit Current Per MPPT	60A
	Start Voltage	350V
	MPPT Voltage Range	200-1000V
	Nominal Voltage	650V
	Number of MPPT	8
	Strings Per MPPT	2
Output(AC)	Nominal AC Output Power	125KW
	Max. AC Output Power	125kVA
	Nominal AC Voltage	230V/400V,3W+PE,3W+N+PE
	AC Grid Frequency Range	50Hz / 60Hz(±5Hz)
	Max. Output Current	181.2A
	Power Factor(Φ)	0.8leading-0.8lagging
	THDi	<3% (Nominal Power)
Efficiency	Max. Efficiency	98.7%
	Euro Efficiency	98.3%
Protection Devices	DC Switch	Yes
	Anti-islanding Protection	Yes
	Output Over Current Protection	Yes
	DC Reverse Polarity Protection	Yes
	String Fault Detection	Optional
	DC/AC Surge Protection	DC Type II;AC Type II
	AC Short Circuit Protection	Yes
	AFCI Function	Optional
	Night SVG Function	Optional
	PID Recovery	Optional
	Insulation Detection	Yes
	Residual Current Monitoring	Yes
General Specifications	Dimensions W x H x D	965mm*700mm*355mm
	Weight	85kg
	Operating Temperature Range	-30~60℃
	Cooling Type	Fan Cooling
	Max. Operation Altitude	5,000 m (> 4,000 mDerating)
	Max. Operating Humidity	0~100%
	IP Class	IP66
	Noise (dB)	≤75dB
	Topology	Transformer less
	Communication	RS485/PLC/WIFI/4G
	Display	LED, Buletooth+APP
	Certification & Standard	EN/IEC62109-1/2; IEC/EN61000-6-2; IEC/EN61000-6-3; IEC/EN61000-6-4; IEC 61727; IEC61683; IEC62116; EN50549-1; VDE-AR-N-4105; CEI 0-16

BLUESUN SOLAR CO.,LTD

Tel:+86 (158) 5821 3997
Fax:+86 (551) 6565 2651
E-mail:info@bluesunpv.com
Add:1499 Zhenxing Road, Shushan District,230031 Hefei,China

BLUESUNPV

*Release BSMXXX 2024-08-Rev01-EN